


SECTION A-A

0-80 UNF THRU
3 PLACES
Ø 1.150
[29.21]

4-40 UNC THRU TO BORE
2 PLACES

MATERIAL: 6061-T6 ALUMINUM, BLACK ANODIZED
OZ Optics reserves the right to change any specification without prior notice.

ALL DIMENSIONS ARE IN INCHES		A	N/A	ORIGINAL ISSUE	C.M.	16-OCT-2019		
REV.	ECR REF#	REV.	ECR REF#	DESCRIPTION	ENG. BY	DATE		
DRAWN BY: P. Summers		DATE: 10/16/2019		UNLESS NOTED OTHERWISE, DIMENSIONS ARE IN INCHES. MILLIMETERS ARE IN SQUARE BRACKETS, AND TOLERANCES APPLY AS SHOWN BELOW. INCHES BASIC DIMENSION DECIMAL PLACES .XX .XXX BELOW 4 ±.01 ±.005 OVER 4 ±.02 ±.01 MILLIMETERS BASIC DIMENSION DECIMAL PLACES .X .XX BELOW 101.6 ±.25 ±.10 OVER 101.6 ±.50 ±.20 ANGULAR DIMENSIONS BASIC DIMENSION X X.X ALL ANGLES ±2.5° ±0.5°	 219 WESTBROOK ROAD OTTAWA, ONTARIO CANADA K0A 1L0 www.ozoptics.com		PART BARCODE #	834
CHECKED BY:		DATE:			DESC.		LASER HEAD ADAPTER #7	
M/S CHECKED BY:		DATE:			DESC.		1.75" OD ADAPTER TO FIT OVER CYLINDRICAL LASERS WITHOUT MOUNTING HOLES	
APVD BY:		DATE:			PART NO.		LPSC-28	
PROJECTION:		DATE:			SCALE:		1.75:1	
CONFIDENTIAL THIS PRINT IS THE EXCLUSIVE PROPERTY OF OZ OPTICS AND MUST BE RETURNED UPON REQUEST. UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.				SURFACE FINISH MILLED PROFILED 125u 63u		SIZE: B DWG.# 4000-0325 SHEET 1 OF 1		