



NOTE:

1) OZ STANDARD APPLICABLE TESTS ARE PERFORMED, DATA IS PROVIDED IN A CoC. CONTACT OZ FOR P/N DETAILS

2) ALL PATCHCORDS ARE PROVIDED WITH DUST CAPS (NOT SHOWN)

A		N/A		ORIGINAL ISSUE		C.M.		09-NOV-2021														
REV.	ECR REF#	DESCRIPTION	ENG. BY	DATE																		
DRAWN BY: P. Summers		DATE: 11/9/2021	UNLESS NOTED OTHERWISE, DIMENSIONS ARE IN MILLIMETERS, INCHES ARE IN SQUARE BRACKETS, AND TOLERANCES APPLY AS SHOWN BELOW.		OZ Optics LIMITED		219 WESTBROOK ROAD OTTAWA, ONTARIO CANADA K0A 1L0		PART BARCODE #: 13238													
CHECKED BY:		DATE:	INCHES		DESC. MULTIMODE FIBER PATCHCORD																	
M/S CHECKED BY:		DATE:	MILLIMETERS		PART NO. QMMJ-3S3S-UVVIS-10/125-3-1		REV A															
APVD BY:		DATE:	ANGULAR DIMENSIONS		SIZE: B		DWG.# 4000-0798		SHEET 1 OF 1													
PROJECTION:		<table border="1"> <tr><th>BASIC DIMENSION</th><th>DECIMAL PLACES</th></tr> <tr><td>.XX</td><td>.XXX</td></tr> <tr><td>BELOW 4</td><td>±.01 ±.005</td></tr> <tr><td>OVER 4</td><td>±.02 ±.01</td></tr> </table>		BASIC DIMENSION	DECIMAL PLACES	.XX	.XXX	BELOW 4	±.01 ±.005	OVER 4	±.02 ±.01	SCALE: 2:1										
BASIC DIMENSION	DECIMAL PLACES																					
.XX	.XXX																					
BELOW 4	±.01 ±.005																					
OVER 4	±.02 ±.01																					
<table border="1"> <tr><th>BASIC DIMENSION</th><th>DECIMAL PLACES</th></tr> <tr><td>.X</td><td>.XX</td></tr> <tr><td>BELOW 101.6</td><td>±.25 ±.10</td></tr> <tr><td>OVER 101.6</td><td>±.50 ±.20</td></tr> </table>		BASIC DIMENSION	DECIMAL PLACES	.X	.XX	BELOW 101.6	±.25 ±.10	OVER 101.6	±.50 ±.20	<table border="1"> <tr><th>BASIC DIMENSION</th><th>DECIMAL PLACES</th></tr> <tr><td>X</td><td>X.X</td></tr> <tr><td>ALL ANGLES</td><td>±2.5° ±0.5°</td></tr> </table>		BASIC DIMENSION	DECIMAL PLACES	X	X.X	ALL ANGLES	±2.5° ±0.5°	SURFACE FINISH				
BASIC DIMENSION	DECIMAL PLACES																					
.X	.XX																					
BELOW 101.6	±.25 ±.10																					
OVER 101.6	±.50 ±.20																					
BASIC DIMENSION	DECIMAL PLACES																					
X	X.X																					
ALL ANGLES	±2.5° ±0.5°																					
<table border="1"> <tr><th>MILLED</th><th>PROFILED</th></tr> <tr><td>125u</td><td>63u</td></tr> </table>		MILLED	PROFILED	125u	63u	CONFIDENTIAL THIS PRINT IS THE EXCLUSIVE PROPERTY OF OZ OPTICS AND MUST BE RETURNED UPON REQUEST. UNAUTHORIZED USE, MANUFACTURE OR REPRODUCTION IN WHOLE OR IN PART IS PROHIBITED.																
MILLED	PROFILED																					
125u	63u																					